Technical Support Instrument

Supporting reforms in 27 Member States

Waste Water Collection and Treatment

Understanding key risks and mitigation factors

Simon Bingham

EPD, Vilnius
13th February 2025







Introduction to the Presenter – Simon Bingham




Regulatory Experience – 30+ years

Permitter, Inspector, Specialist & Manager Implementer of new legislation (Waste, Water, Integrated, Radioactive) Developer of systems (Permitting, Risk & Inspection Frequency etc) Trainer

International Experience – 19+ years

Project Executive & Project Manger of numerous technical projects
Team Leader of 15+ organizational reviews
IMPEL Board Member & Expert Team Leader for 9 years
Worked in Europe, America, Asia & Africa





Question: How many years have you worked on the topic of water regulation?

Action: Line up from least to most experience



Rough Timings	Wastewater Collection & Treatment Agenda	
1330 -	Introduction	
- 1415	Wastewater Collection Networks – CSOs & EOs (& complaints)	
1415 - 1430	Break	
1430 - 1545	WWTW - Preliminary, Primary & Secondary Treatment	
1545 - 1600	Break	
1600 -	WWTW -Treatment continued	
-	Risk & planning	
- 1700	Enforcement response	
1700	End	



My rules of engagement

- 1. You can ask questions at any time I will of you ☺!
- There are no daft or stupid questions (don't assume others all know the answers already they probably don't help them out by asking! I assume there is a knowledge range in the room
- **3.** Respect each other (don't talk over each other)
- 4. Have fun
- **5.** Any questions about this?



Question:

Is there any specific areas you want me to cover or questions you would like me to answer this afternoon?



Introduction - (The big issues)

- 1. Describe your permits. What do they cover?
- 2. Describe your inspection process. Do you use the permit as part of the inspection. Do you check every permit condition?
- 3. How do you choose the sites to inspect?
- 4. How long does an inspection take?



If you were to inspect this WWTW, what would be the most important part of the inspection? And why?



1. Impact on the receiving watercourse

2. Quality of effluent discharge

3. Some elements of the treatment process



The environment is our primary focus and reason for existence

What is the impact on the receiving watercourse?

- Sewage Solids
- Presence of excessive sewage fungus
- Excessive Foaming
- Significant discolouration
- Visible oil or grease
- Pooling of effluent/ adequate dilution and dispersal
- Compare upstream and downstream
- Describe river flow conditions and colour etc



Serious impact of sewage solids





Sewage Fungus – Bioindicator of organic pollution



Natural – Okay



Effluent fed - Unacceptable

- It is actually a complex biomicrobial mat and not a fungus it feeds on nutrients
- Not just sewage agricultural runoff, papermill, airport de-ice fluid etc



Poorly sited / performing effluent discharge





How would we design a checklist to capture 'impact on the receiving watercourse'?

- Sewage Solids
- Sewage fungus
- Foaming
- Discolouration
- Visible oil or grease
- Pooling of effluent/ adequate dilution and dispersal



Personal Protective Equipment & Risk Assessment (You can't inspect if you are dead!)

PPE will vary based on RA

- Protective Footwear
- High-Vis Jacket
- Gloves & Safety Glasses (Mask?)
- Ability to store PPE safely / change of clothes
- Ability to clean hands etc
- Hard Hat
- Life jacket
- Inoculations Hep A & B, Tdap booster etc



What sort of risks are you likely to encounter?



The primary EU Directives that impact Wastewater Treatment & Collection

Dir. Number	Directive Name	Covers
91/271/EEC	Urban Wastewater Treatment Directive	Minimum standards, population thresholds, discharge limits
91/676/EEC	Nitrates Directive	Protects from nitrate pollution, stricter stds in NVZ
2000/60/EC	Water Framework Directive	Prevent waterbody deterioration, achieve good status
2006/7/EC	Bathing Water Directive	Prevents impact, requires microbiological monitoring
2008/105/EC	Environmental Quality Standards Directive	Standards set
2010/75/EU	Industrial Emissions Directive	Large WWTW & industrial effluents, sludge incineration
2011/92/EU	Environmental Impact Assessment Directive	Needed for new or expanded WWTWs
2024/3019	Urban Wastewater Treatment Directive (recast)	Sets future WWTW standards

Q1: Many of these Directives have been recast or amended. What came into force on the 1st January 2025

Q2: What is the primary document that we inspect against called? The Permit




Wastewater Collection



Where is Vilnius WWTW located?




Gravity systems where possible







The ideal is a separate collection systems for sewage and surface water








Where gravity systems are not possible you have to pump



Emergency Overflow at Pumping Station (discharge to prevent the network flooding)



What does good look like:

- **Back-up power (uncommon)**
- Flow monitoring
- **Telemetry**
- Requirement to clean watercourse

(all should be covered in the permit)

Raw sewage (unlikely to be screened)



Visible impact of untreated sewage on a watercourse (after the discharge has stopped)



Top 5 most common rubbish items flushed down a toilet


- Q-Tips (cotton buds)
- Condoms
- Sanitary pads/tampons

- Contact lenses
- Wet wipes

Inspection Tips

- Upstream & Downstream ass.
- Photographs (methodology?)
- Can bag physical evidence





What does good look like:

- Flow monitoring
- Telemetry
- Requirement to clean watercourse
- Temporary storage (rare)
- Screens (mechanical)

(all are permit conditions)











What is the most important aspect of inspecting a CSO or EO? They should only operate when necessary! i.e. storms or emergencies











SW system - wrong connection? - follow the bubbles (or oil for interceptor problems)







Searching for the source: Game of elimination, lifting manholes




What would you put in a checklist to cover the wastewater collection system?



The Wastewater Treatment Works (WWTW)

The key stages of effluent treatment



Note: some stages may not be present on your site inspection



Primary Treatment


Sludge Treatment



Secondary Treatment

Preliminary Treatment

Note: size varies based on capacity of the works, levels of treatment vary based on WWTD & the receiving environment





- Pumps
- Overflows (storm tanks?)
- Screens
- Flow data



Inlet pumps – needed to achieve gravitational head (if needed at all)






Note: There should be duty and standby pumps
There will be an EO associated with the pumps



Combined Sewer Overflow at the works



CSO basics:

- Set at x litres per second
- Based on multiples of Dry Weather Flow (DWF)
- Often set at 3 or 6DWF


What does good look like:

- Screens (cleaned)
- Move to 6mm 3D screens (smaller clog more often)

(all should be in permit conditions)




Perforated band CSO (storm tank and discharge to the environment)



What does good look like:

- Screenings returned to main flow
- Automated cleaning of screens

(all should be in permit conditions)



What does good look like:

- Screens should be clean when not operating
- CSOs should not be operating in dry weather*

(all should be in permit conditions)



CopaSac often used on smaller CSOs



What does good look like:

- Sacks manually removed and replaced after operation
- Sacks should be appropriately disposed off
- Access should allow easy checking and replacement

(should be in permit conditions)


 Should be no discharge in dry weather – only during storm event & when incoming flow to works >3DWF


- As storm increases
 - Hydraulic capacity of WWTW exceeded
 - Overflow to storm tank (captures most polluting 'first flush')
 - As storm continues watercourse flow increases & eventually settled storm sewage overflows to watercourse
- The storm tank is emptied back into WWTW as flow allows.





Storm tank & CSOs on a WWTW





- Objective is to protect works from larger items & prevent contamination of environment & potentially sewage sludge
- Types
 - Bar screens manual or automatically raked
 - Band screens
 - Drum
- Often 6mm inlet at large modern STWs
- Screenings
 - Remove, compact and dispose skip/bag to landfill or incineration
- Grit Removal
 - Removes grit, small stones that could damage pumps



Manually raked screen (older systems or used in conjunction with additional methodology)



What does good look like:

- Difficult to keep clean, however, they require regular cleaning to stop blockage. There should be no significant build-up
- Waste should be appropriately disposed off

(should be in permit conditions)

Band screen (rotates)







Rotating drum screen





Screenings & grit collection



What does good look like:

- Waste is collected in a controlled way
- Waste is appropriately disposed off

(requirement should be in permit conditions)

Minor non-compliance



Grit removal (another minor non-compliance)





Telemetric sensors (event monitors)



What does good look like:

- Telemetric sensors in place as required.
- Here it would pick up a rise in influent which would show the screen is blocked

(requirement should be in permit conditions)



Serious issue (Inlet screens completely blocked – effluent backing up)





Evidence of previous issues – require clean-up





FFT is usually 3DWF (more is better)

The exact volume should be in the permit

The volume passed forward to FFT should always be checked and recorded during inspection

Be aware of the economic incentive not to treat 3DWF!

Flow Measurement and Flow Rate

Most licences now have a Dry Weather Flow limit on the influent and there may also be flow related conditions on CSO's within the works. A good permit will not only give limits but also describe how & where the data can be accessed on site

Inlet Autosampler


UWWTD requires flow-proportional or time-based sampling for some WWTW. Autosamplers are often used to comply with this requirement. Is it working? Temperature?

Pre-Treatment

This may include chemical dosing to assist the treatment process e.g. assist suspended solid removal, nutrients etc


- Pumps
- Overflows (storm tanks?)
- Screens
- Flow data
- Autosampler (if required)
- Pre-treatment (if required)





Primary objective: Remove organic matter

Allow solids to settle, forming sludge, while grease and oils etc float to the surface for removal



- Can be circular or rectangular
- Reduce suspended solids
 by 50 to 80%
- Reduce BOD by typically 30%
- Manual or automatically desludged
- Reduces bacterial load by 25-50%



How a Primary Settlement Tank (PST) works





PST Scum Board (or Scum Baffle)








Retention: 1.5 - 2 hours



What does good look like:

- Arm rotating
- Floating scum (including fat & oils) remains on the inside of the Scum Board
- Floating scum collected and removed from skimmer
- Channels free from sewage fungus (often brushed). These are sometimes painted white to highlight






Rectangular PST(works the same way as circular tanks)






Floating scum carried over (Is this a non-compliance?)





Poor maintenance (Is this a non-compliance?)






Septic tank – Primary treatment for a rural location

Use: Where there is no access to a centralised sewer network – single house to a small rural settlement

- Works by separating solids & liquids (shown on diagram next slide)
- Anaerobic digestion bacteria break down organic matter in the absence of oxygen, reducing sludge volume
- It does not fully treat wastewater
- It does not remove nutrients
- It requires limited maintenance, however, should be emptied (3-5 years domestic)
- You have to be careful what you put into it
- It should discharge to a soakaway or partial soakaway



Septic Tank (locally built rectangular or off-the-shelf 'onion') – Primary Treatment Only






Primary Treatment Checklist





Secondary Treatment in the form of Biological Treatment



Biological Treatment – 3 types of process

- Suspended Growth Systems
- Attached Growth Systems
- Advanced Biological Nutrient Removal (BNR)

- Microorganisms suspended in water
- Microorganisms grow on surfaces
- Microorganisms remove key nutrients (e.g. enhanced nitrogen removal)

Varied, potentially complex

Fortunately for us there is little to check during routine inspection!

Reduces bacterial load by 80-99%


1. Suspended Growth Systems

- High organic matter removal (BOD & COD reduction)
- Some biological nutrient removal (nitrogen)
- Can be used for municipal and industrial wastewater (scalable & modifiable)
- Can handle variable loads flow & load (seasonal or industrial variations)
- Disadvantages include high energy costs & requires careful sludge management

Q. All things being equal does municipal sewage change its strength during the year?



Activated Sludge Process (2 common approaches)





Diffused Air Whisk

Retention: 6-8 hours longer for ammonia removal




Mixed Liquor Suspended Solids (MLSS)

MLSS refers to the concentration of suspended solids (microorganisms, organic and inorganic particles) in the aeration tank of an activated sludge system. It represents the total amount of microrganisms available to break down organic pollutants

- It is a key parameter used by WWTW operators to monitor and control the process
- Measured by filtering, drying & weighing to determine solid concentration in mg/l
- Helps operators optimize aeration. MLSS controlled by return activated sludge rate
- Higher MLSS can give better treatment performance but could cause poor sludge settling
- Lower MLSS may reduce treatment efficiency leading to higher BOD and ammonia in the effluent
- Typical MLSS Range 1500-2000 mg/l but 4000 mg/l for nitrification (ammonia removal)

Activated Sludge (AS) Process & Sludge Collection



Most settled sludge eturned to AS inlet (RAS) since need the bacterial culture. Excess sludge (Surplus AS or SAS) removed from process, either passed to inlet to PST for settlement or at FST. Goes to sludge holding tanks for treatment and disposal

2. Attached Growth Systems

- More resistant to shock loads
- Lower sludge production than suspended growth systems
- Potentially very low energy requirement
- Less day-to-day maintenance
- Disadvantages: Can clog and less good at nutrient removal



Percolating or trickling filters



- Much bigger footprint than activated sludge
- Some motorised but often work on effluent pressure (high head pressure required)
- Old proven technology (1900s)

- Media: stones or plastic
- Normally 2m+ deep (weight of media limits)
- Approximately 30-minute retention


Can recirculate in dry weather



*Tipping bucket diagram



Percolating filter schematic





Spot the issue (is it a non-compliance?)



*Let's talk about flies



A more obvious maintenance issue (is it a non-compliance?)






Package plants – common biological treatment for rural developments (<1000 pe)



- RBC Rotating Biological Contact
- Slow rotating discs
- Bacterial film on discs
- No flies, limited odour
- Don't work when power off





- Moving
- Light brown to grey film



Final Settlement Tank (FST)



 Half the size of PST as sludge more easily settled (retention approx. 1.5 hours)

 The settlement tank after a percolating filter is called a humus tank – different sludge.





 Used after activated sludge process to remove solids









Carryover of sludge from the activated sludge process to the final settlement tanks



Non-compliance?



Secondary Treatment Checklist



 Should be a requirement in permit for a clearly marked location (e.g. map or an actual sign at location) where a mixed sample can be taken.



Single white tile – an inspector's friend






Final discharge with upstream & downstream 'enforcement samples'





Tertiary treatment (a few slides only on most common options)



Objective to improve or 'polish' quality of secondary treated effluent by removing suspended solids, BOD, nutrients, ammonia or pathogens





- Sand filters effectively a filter which gets blocked by particulates – so need to backwash to clean
- Pumping energy cost
- Can remove 70% of SS and BOD




- Sustainable
- Low maintenance
- No power but not cheap
- Need to control level of sewage

- Micro-strainers like sand filters & reed beds designed to reduce SS/BOD (often are rotating drums – require back washing)
- Chemical dosing used for nutrient removal (P) e.g. ferric sulphate dosing
- **Disinfection** used to reduce bacterial load for discharges that could impact bathing beaches or shellfish (UV & ozone chlorine not favoured due to the productions of chloramines which are toxic to aquatic life
- Plastic media towers (like percolating filters but finer grade media) used to reduce ammonia. Nitrifying bacteria are added.



Somewhere closer to home – what do you see?





The hydrology of the discharge



Time to be a bit more strategic

Does size matter?


How do you prioritise what you are going to inspect?

Do you have to inspect every site?

There should be a <u>reason</u> for every inspection

My priority list (in no particular order):

- Currently causing pollution or is significantly non-compliant
- Actual or high potential to impact a sensitive area/site
- Where improvement in this site would cause (or significantly increase water quality towards) good status (WFD) to be achieved
- Where the site is causing or significantly contributing to a downgrade in WQ
- Other strategic priorities



Technical Support Instrument

Supporting reforms in 27 Member States

This presentation was produced with the financial assistance of the European Union. Its content is the sole responsibility of the authors. The views expressed herein can in no way be taken to reflect the official opinion of the European Union.

The project is funded by the European Union via the Technical Support Instrument, managed by the European Commission Directorate-General for Structural Reform Support.



© European Union 2023

Unless otherwise noted the reuse of this presentation is authorised under the <u>CC BY 4.0</u> license. For any use or reproduction of elements that are not owned by the EU, permission may need to be sought directly from the respective right holders.